



The Concise Latest Report on the Advantages and Disadvantages of Pure Biodiesel (B100) on Engine Performance: Literature Review and Bibliometric Analysis

Muji Setiyo^{1,3*}, Dori Yuvenda^{2,3}, Olusegun David Samuel^{4,5}

¹Department of Automotive Engineering, Universitas Muhammadiyah Magelang, Indonesia

²Department of Automotive Engineering, Universitas Negeri Padang, Indonesia

³Center of Energy Studies for Society and Industry, Universitas Muhammadiyah Magelang, Indonesia

⁴Department of Mechanical Engineering, Federal University of Petroleum Resources, Delta State, Nigeria

⁵Department of Mechanical Engineering, University of South Africa, Science Campus, Private Bag X6, Florida 1709, South Africa

Correspondence: E-mail: muji@unimma.ac.id

ABSTRACT

Currently, many countries are promoting B100 as the main fuel for diesel engines towards the transition to 100% renewable energy applications. However, due to its properties, B100 has both advantages and disadvantages to replace diesel oil. Therefore, a bibliometric analysis was carried out to evaluate the performance and emissions of a diesel engine with the B100 being tested on a multi-cylinder diesel engine for cars. Unfortunately, only 12 of the 127 selected articles are eligible to be reviewed in detail and none of them discusses all the key performance of diesel engines which include Brake Thermal Efficiency (BTE), Specific Fuel Consumption (SFC), Cylinder Pressure (CPs), Heat Release Rate (HRR), NO_x, and smoke. Through data synthesis, we found that the use of B100 provides advantages in engine noise, thermal efficiency, specific fuel consumption, and emissions under certain engine loads. On the other hand, it also has the potential to result in poorer performance, if there is no modification to engine components and the addition of additives. As a recommendation, the results of this analysis provide a guide for further research to examine the use of B100 with all diesel engine performance variables. Research paths can be developed with the wider potential to provide new arguments on various diesel engine technologies, engine capacities, B100 raw materials, and test environments.

ARTICLE INFO

Article History:

Submitted/Received 24 Apr 2021

First revised 24 May 2021

Accepted 28 Jul 2021

First available online 30 Aug 2021

Publication date 01 Dec 2021

Keyword:

B100,

Bibliometric analysis,

Brake thermal efficiency,

Cylinder pressure,

Heat release rate,

NO_x,

Smoke,

Specific fuel consumption.

1. INTRODUCTION

In the last decade, the issue of global warming and climate change continues to strengthen and it is associated with the use of oil-based fuels (Franta, 2021; Ginanjar Ahmad Zakky, 2020; Sinaga, 2020) which have more environmental risks from exploration, transportation, production, distribution, and consumption (Chettouh et al., 2016). Natural damage in oil drilling areas (Harnani, 2018), cases of oil spills in the Gulf of Mexico and the Atlantic are other examples of environmental threats from fossil fuels (Bhattarai et al., 2011; Soares et al., 2020). In fact, a greater risk is reported in Nigeria, where oil spills are significantly correlated with humanitarian tragedy (Bruederle & Hodler, 2019).

On the other hand, efforts to find and implement alternative energy are also a strong challenge for many countries, regarding availability, prices, environmental balance, and also policies (Hadiyanto et al., 2020; Kaniapan et al., 2021; Panoutsou et al., 2021; Yusoff et al., 2021). The sustainability of the industrial and transportation sectors with renewable fuels continues to be carried out through the substitution of fossil fuels, either with a fully dedicated system or with a bi-fuel system or a hybrid system (Anderhofstadt & Spinler, 2020; Shao & Dessouky, 2020). The transition to the adoption of 100% renewable energy is a complex process, not only on technical issues, but also on political, economic, and social issues. For example, the expansion of the use of bioethanol will face the availability of land for food production (de Souza Ferreira Filho & Horridge, 2014).

For the transportation sector, the expansion of biodiesel for the internal combustion engine (IC) is more prospective than bioethanol for spark ignition (SI) engines. The properties of biodiesel, which are closer to diesel oil at competitive prices, make it a reasonable choice for a 100% transition. Raw materials for biodiesel

production are also increasingly diverse, with the discovery of superior varieties of local plants that have been proven to produce good biodiesel, including:

- (i) Palm (Arifin et al., 2019; Marlina et al., 2020)
- (ii) Coconut (Nanlohy et al., 2020),
- (iii) Nyamplung/Calophyllum inophyllum L. (Fadhlullah et al., 2015; Fauzan et al., 2020; Pambudi et al., 2021),
- (iv) Jatropha (Fajar & Setiapraja, 2014; Silitonga et al., 2016),
- (v) Kemiri sunan/Reutealis trisperma (Supriyanto et al., 2019; Supriyadi & Purwanto, 2018),
- (vi) Waste cooking oil (Ayu et al., 2019; Hadiyanto et al., 2020),
- (vii) Rubber (Supriyanto et al., 2019), and
- (viii) Plastic-derived fuels (Sunaryo et al., 2021).

Especially for waste cooking oil, in addition to producing biodiesel, it also contributes to the environment by reducing the potential for waste from restaurants and the cooking oil-based food industry (Kolakoti et al., 2021).

The technology for biodiesel production which includes starting materials, pre-treatment methods, reactors, and processing methods, catalysts, and testing methods is also developing rapidly (Hariyanto et al., 2021; Mahlia et al., 2020; Zetra et al., 2021; Hidayat et al., 2022). On the other hand, cleaner ethanol (Vohra et al., 2014; Wahyu et al., 2019; Waluyo et al., 2020) with its different properties from gasoline and the relatively large price difference, requires major modifications to the engine components and increases driving operating costs, making it weaker in terms of market acceptance (Mudombi et al., 2018).

As an alternative fuel with all its advantages, biodiesel also has several disadvantages, including a very high flash point causing delayed ignition, cold flow properties, and poor oxidation stability contributing to its disadvantages (Atabani et al., 2012; Bukkarapu, 2019; Firoz, 2017).

Therefore, blending biodiesel with diesel oil is widely used to reduce its disadvantage. Although currently the use of pure biodiesel (B100) is the future target market and is commercially available, B100 research reports on multi-cylinder car engines are still limited, they are dominated by testing on low-speed single-cylinder engines (Ajith *et al.*, 2021; Altaie, 2020; Arun *et al.*, 2020; Kumar & Subramanian, 2020; Örs *et al.*, 2020; Rameshbabu *et al.*, 2020; Singh *et al.*, 2020; Viswanathan *et al.*, 2020; Yatish *et al.*, 2021). Although the working principle is the same, car engines have complexities related to performance.

In addition, the performance of diesel engines is also more complex than gasoline engines, which include Brake Thermal Efficiency (BTE), Specific Fuel Consumption (SFC), Cylinder Pressure (CPs), Heat Release Rate (HRR), NO_x, and Smoke. Partial engine testing with some parameters, of course, cannot measure the overall performance of the B100, considering that these parameters influence each other. The reason this parameter is studied in depth is that the parameters of BTE and SFC are part of engine performance which are very important to analyze because they are related to the use of fuel in diesel engines. As it is known that the main purpose of using biodiesel fuel is to replace diesel fuel to reduce fossil fuel consumption. Likewise, parameters of the cylinder pressure and the heat release rate are representations of engine power that describe the combustion process in the cylinder so that knowing these two parameters can describe engine performance. The parameters of NO_x and smoke emissions are important reviewed in


this article that diesel engines contribute greatly to producing these emissions so that this is a concern in the world by setting thresholds for these emission levels as issued by the Ministry of Environment and Forestry and the European Union.

Therefore, this article presents a concise literature review and bibliometric analysis on the advantages and disadvantages of the B100 which was tested on a multi-cylinder diesel engine with a capacity above 1 liter, which is considered more representative of real application conditions than single or twin cylinder engines. The literature were reviewed from search engine (Azizah *et al.*, 2021). Then, the references and limitations reviewed are presented in detail in **Table 1** (see method section).

As the uniqueness of this work, we used VOSviewer to determine the topics studied (bibliometric analysis), as has been practiced by Hamidah *et al.* (2020) and Husaeni and Nandiyanto (2022). Key performance of diesel engine which includes Brake Thermal Efficiency (BTE), Specific Fuel Consumption (SFC), Cylinder Pressure (CPs), Heat Release Rate (HRR), NO_x, and Smoke is used in the search method for articles in the Scopus database. The iteration results by VOSviewer show they have a strong relationship, as presented in **Figure 1**. Therefore, the specific purpose of this work is to analyze the advantages and disadvantages of B100 in diesel engines by considering the combustion process which includes cylinder pressure, heat release rate, and engine performance including thermal efficiency, specific fuel consumption, and exhaust emissions including nitrogen oxide and smoke emissions.

Table 1. Limitations of searching criteria.

No	Searching criteria	:	Limitation
1.	Database	:	Scopus
2.	Search within	:	Article title, abstract, keyword
3.	Search document	:	B100, performance, emission
4.	Type of access	:	All (All Open Access, Gold, Hybrid Gold, Bronze, Green)
5.	Year	:	2017-2021
6.	Subject area	:	Engineering, Energy, Chemistry, Environmental Science, Chemical engineering
7.	Document type	:	Article
8.	Publication stage	:	Final
9.	Source title	:	All (not specified)
10.	Keywords	:	All (not specified)
11.	Affiliation	:	All (not specified)
12.	Funding sponsor	:	All (not specified)
13.	Country	:	All (not specified)
14.	Source type	:	Journal
15.	Language	:	English
16.	Date access	:	June 20, 2021

**Figure 2.** Content selection process and criteria.

3. RESULT AND DISCUSSION

3.1. Data Synthesis

This section describes the data synthesis from previous studies related to engine performance and emissions in diesel engines using B100. The key performance characteristics of diesel engines (Balasubramanian *et al.*, 2021) including Brake Thermal Efficiency (BTE), Specific Fuel Consumption (SFC), Cylinder Pressure (CPs), Heat Release Rate (HRR), NO_x, and Smoke were examined in 12 reviewed articles. The results of the synthesis data review are

described in **Table 2** and **Table 3**, respectively.

Unfortunately, only 12 of the 127 selected articles are eligible to be reviewed in detail and none of them discusses all the key performance of diesel engines which include Brake Thermal Efficiency (BTE), Specific Fuel Consumption (SFC), Cylinder Pressure (CPs), Heat Release Rate (HRR), NO_x, and smoke, all article discusses partially. The data testing scope is presented in **Figure 3**.

Table 2. Review of data synthesis from engine performance characteristics and emissions using pure biodiesel (B100).

No	Raw material, Refs	Engine use	Method and Variable	Main finding (conclusion remark)
1.	African Pear (Dyacrodes edulis) Seed Oil (Esonye et al., 2019)	Perkins 4:108	Experimental research methods and statistical tests using ANN. The variables studied included engine load (5-40 Nm), biodiesel blends (B20-B100), and engine speed (1500-3500 rpm).	<ol style="list-style-type: none"> 1. Higher thermal efficiency than diesel oil at all engine loads. 2. Lower SFC than fossil diesel at all engine loads. 3. Higher NOx emission levels than diesel oil at all engine loads.
2.	Coconut (Thangaraja & Srinivasan, 2019)	3.298L, 70 kW	Experimental research with variables including BMEP 1.7-8.4 bar and an engine speed of 1000-2000 rpm.	<ol style="list-style-type: none"> 1. Peak cylinder pressure is slightly lower than diesel oil at low and high loads. 2. Peak heat release rate is slightly lower than diesel oil at low and high loads. 3. Higher thermal efficiency than diesel oil at all engine loads. 4. NOx levels are lower at low loads, while at medium and high loads the Nox is higher than diesel oil.
3.	Crude palm oil (Ge et al., 2020)	4-cylinder CRDI	Experimental research with variables including EGR rate (0-20%), fuel injection timing (14°-34°BTDC), and engine load (35 and 105 Nm).	<ol style="list-style-type: none"> 1. The peak cylinder pressure does not show a significant difference from diesel oil at low and high loads. 2. The peak heat release rate did not show a significant difference from diesel oil at low and high loads. 3. Higher SFC than diesel oil at low and high loads. 4. NOx is higher than diesel oil at low and high loads.
4.	Waste cooking oil (García-Martín et al., 2018)	2.0 TDI 140 hp	Experimental research at an engine speed of 1000-3000 rpm and engine load of 15%-45%.	<ol style="list-style-type: none"> 1. SFC is higher than diesel oil at low and medium loads. 2. NOx is higher than diesel oil at low and medium loads.
5.	Safflower (Isik, 2021)	NWK22	Experimental research on biodiesel with the addition of alcohol (20%) and at engine load of 25-75%.	<ol style="list-style-type: none"> 1. Lower cylinder pressure than diesel oil at medium load (75%). 2. Lower heat release rate than diesel oil at medium load (75%). 3. Lower thermal efficiency than diesel oil at low load, but higher at medium load. 4. Higher SFC than diesel oil at all engine loads. 5. NOx is higher than diesel oil at all engine loads.
6.	Safflower (Aydin, 2020)	2.4 L Diesel	Experimental research on biodiesel with the addition of methyl proxitol and ethyl proxitol catalysts (10%) and at engine load of 20-60%.	<ol style="list-style-type: none"> 1. Lower cylinder pressure than diesel oil at medium load (60%) 2. Lower heat release rate than diesel oil at medium load (60%) 3. Thermal efficiency values are lower than diesel oil at low and medium loads. 4. SFC is higher than diesel oil at low and medium. 5. NOx is higher than diesel oil at low and medium loads.

Table 2 (Continue). Review of data synthesis from engine performance characteristics and emissions using pure biodiesel (B100).


No	Raw material, Refs	Engine use	Method and Variable	Main finding (conclusion remark)
7.	Soybean (Tosun & Özcanlı, 2021)	4D34-2A	Experimental research with the addition of nanoparticles (Al ₂ O ₃) and hydrogen to biodiesel, at an engine speed of 1200-2800 rpm.	<ol style="list-style-type: none"> 1. Higher SFC than diesel oil at full load. 2. NOx higher than diesel oil at full load.
8.	Soybean (Santos <i>et al.</i> , 2017)	D225-6	Experimental research on the fuel mixture (B5-B100) was carried out at engine load of 9, 18, and 27 kW	<ol style="list-style-type: none"> 1. Higher SFC than diesel oil at low and medium loads. 2. NOx higher than diesel oil at low and medium loads.
9.	Vegetable-based (Abdalla, 2018)	Ford 1.8L	Experimental research on a biodiesel blend (B25-B100) and BMEP 1-6 bar.	<ol style="list-style-type: none"> 1. Higher thermal efficiency than diesel oil at all engine loads. 2. Lower SFC than diesel oil at all engine loads. 3. Lower NOx than diesel oil at all engine loads. 4. Smoke was higher than diesel oil at low and medium, while lower levels were found at high loads.
10.	Waste cooking oil (Ghadikolaie <i>et al.</i> , 2019)	4434L	Experimental research on biodiesel blends (B0-B100) and the engine load of 5-95%,	<ol style="list-style-type: none"> 1. Higher thermal efficiency than diesel oil at all engine loads. 2. Higher SFC than diesel oil at all engine loads. 3. NOx is higher than diesel oil at all engine loads. 4. Lower smoke than diesel oil at all engine loads.
11.	Waste cooking oil (Odibi <i>et al.</i> , 2019)	Cummins ISBe220 31	Experimental research with the addition of triacetin (4, 5, 8, and 10%) to the B100 at engine speeds of 1472, 1865, and 2257 rpm; and at engine load (25-100%).	<ol style="list-style-type: none"> 1. Higher thermal efficiency than diesel oil at all engine loads. 2. Higher SFC than diesel oil at all engine loads.
12.	Waste cooking oil (Hojati & Shirneshan, 2020)	OM 355	Experimental research and thermodynamic simulation using MATLAB on variables that include: <ol style="list-style-type: none"> a. Biodiesel blends (B0-B100) b. Compression comparison (14-18) c. Engine load (25-100%) 	<ol style="list-style-type: none"> 1. Lower cylinder pressure than diesel oil at high load (100%). 2. Lower heat release rate than diesel oil at high load (100%). 3. Lower thermal efficiency than diesel oil at all engine loads. 4. NOx higher than diesel oil at all engine loads.

Table 3. Testing scope of the selected reviewed articles

No	Raw material, Refs	Engine use	Method and Variable	Testing scope					
				BTE	SFC	CPs	HRR	NOx	Smoke
1.	African Pear (Dyacrodes edulis) Seed Oil (Esonye et al., 2019)	Perkins 4:108	Experimental research methods and statistical tests using ANN. The variables studied included engine load (5-40 Nm), biodiesel blends (B20-B100), and engine speed (1500-3500 rpm).	Yes	Yes	No	No	Yes	No
2.	Coconut (Thangaraja & Srinivasan, 2019)	3.298L, 70 kW	Experimental research with variables including BMEP 1.7-8.4 bar and an engine speed of 1000-2000 rpm.	Yes	No	Yes	Yes	Yes	No
3.	Crude palm oil (Ge et al., 2020)	4-cylinder CRDI	Experimental research with variables including EGR rate (0-20%), fuel injection timing (14°-34°BTDC), and engine load (35 and 105 Nm).	No	Yes	Yes	Yes	Yes	No
4.	Waste cooking oil (García-Martín et al., 2018)	2.0 TDI 140 hp	Experimental research at an engine speed of 1000-3000 rpm and engine load of 15%-45%.	No	Yes	No	No	Yes	No
5.	Safflower (Isik, 2021)	NWK22	Experimental research on biodiesel with the addition of alcohol (20%) and at engine load of 25-75%.	Yes	Yes	Yes	Yes	Yes	No
6.	Safflower (Aydın, 2020)	2.4 L Diesel	Experimental research on biodiesel with the addition of methyl proxitol and ethyl proxitol catalysts (10%) and at engine load of 20-60%.	Yes	Yes	Yes	Yes	Yes	No
7.	Soybean (Tosun & Özcanlı, 2021)	4D34-2A	Experimental research with the addition of nanoparticles (Al ₂ O ₃) and hydrogen to biodiesel, at an engine speed of 1200-2800 rpm.	No	Yes	No	No	Yes	No
8.	Soybean (Santos et al., 2017)	D225-6	Experimental research on the fuel mixture (B5-B100) was carried out at engine load of 9, 18, and 27 kW	No	Yes	No	No	Yes	No

Table 3 (Continue). Testing scope of the selected reviewed articles.

No	Raw material, Refs	Engine use	Method and Variable	Testing scope					
				BTE	SFC	CPs	HRR	NOx	Smoke
9.	Vegetable-based (Abdalla, 2018)	Ford 1.8L	Experimental research on a biodiesel blend (B25-B100) and BMEP 1-6 bar.	Yes	Yes	No	No	Yes	Yes
10.	Waste cooking oil (Ghadikolaie et al., 2019)	4434L	Experimental research on biodiesel blends (B0-B100) and the engine load of 5-95%,	Yes	Yes	No	No	Yes	Yes
11.	Waste cooking oil (Odibi et al., 2019)	Cummins ISBe220 31	Experimental research with the addition of triacetin (4, 5, 8, and 10%) to the B100 at engine speeds of 1472, 1865, and 2257 rpm; and at engine load (25-100%).	Yes	Yes	No	No	No	No
12.	Waste cooking oil (Hojati & Shirneshan, 2020)	OM 355	Experimental research and thermodynamic simulation using MATLAB on variables that include: a. Biodiesel blends (B0-B100) b. Compression comparison (14-18) c. Engine load (25-100%)	Yes	No	Yes	Yes	Yes	No

**Figure 3.** Testing scope comparison of the selected reviewed articles.

3.2 Discussion

3.2.1 Standard of B100

Like other fuels, biodiesel is not standardized by its material, but it is standardized by its properties. Biodiesel standards were developed in the 1990s to facilitate the growing use of alkyl esters-based biodiesel and its mixes as automobile

fuels. In 1999, American Society for Testing and Materials (ASTM) International issued PS121, a preliminary standard for biodiesel. In 2002, the first ASTM standard (ASTM D6751) was adopted. **Table 4** shows the selected ASTM International requirements for B100, where these specifications are regularly updated and modified.

3.2.2 Combustion characteristics

3.2.2.1. Cylinder pressure and heat release

The use of B100 resulted in lower cylinder pressure and heat release rate than diesel oil and blended biodiesel especially at low and medium loads, as shown in previous studies (Aydin, 2020; Hojati & Shirneshan, 2020; Isik, 2021). Although it was tested with different types of B100, it also showed the same trend.

Isik (2021) explained that the peak of cylinder pressure and heat release rate with the use of diesel fuel (USLD) reached 80.55 bar and 69.15 J/o respectively at engine load is 75%, while the use of B100 fuel, the value was much lower. Hojati & Shirneshan (2020) also explained that the cylinder pressure drop reached 10.5% with the use of B100 fuel. Research from Aydin (2020) found that the heat release rate using diesel fuel was 73.01 J/CAD and the use of B100 fuel produced a value of 64.767 J/CAD at a load of 10.8 kW.

Aydin (2020) explained that the cylinder pressure drop in the B100 application was caused by poor atomization and mixing due to its high viscosity and density, which resulted in a longer ignition delay and shorter combustion duration. Hojati and Shirneshan (2020) also explained that the cylinder pressure drop was due to the lower LHV of biodiesel than diesel oil. The application of B100 causes the peak cylinder pressure to be closer to the top dead center (TDC) due to the higher cetane number so that the combustion process is more advanced. Therefore, increasing the compression ratio (CR) can increase the cylinder pressure to increase the temperature at the start of the injection, thereby increasing the rate of heat release. Figure 4 shows the compression ratio (18:1) can increase cylinder pressure in the B100 application by 18.3%.

Table 4. Standard for B100.

Property	Reference Test Methods*	Grade	Grade	Grade	Grade
		No.1-B S15	No.1-B S500	No.2-B S15	No.2-B S500
Sulfur, % mass (ppm), max	D5453	0.0015 (15)	0.05 (500)	0.0015 (15)	0.050 (500)
Cold soak filterability, s, max	D7501	200	200	360	360
Monoglycerides, % mass, max	D6584	0.40	0.40	-	-
Requirements for All Grades					
Calcium and Magnesium, combined, ppm, max	EN14538	5	5	5	5
Flash point (closed cup), °C, min	D93	93	93	93	93
Alcohol Control: One of the following must be met					
(1) Methanol content, mass%, max	EN14110	0.2	0.2	0.2	0.2
(2) Flash point, °C, min	D93	130	130	130	130
Water and sediment, % volume, max	D2709	0.050	0.050	0.050	0.050
Kinematic viscosity, mm ² /s, 40°C	D445	1.9-6.0	1.9-6.0	1.9-6.0	1.9-6.0
Sulfated ash, % mass, max	D874	0.020	0.020	0.020	0.020
Copper strip corrosion	D130	No. 3	No. 3	No. 3	No. 3
Cetane number, min	D613	47	47	47	47
Cloud point, °C	D2500	Report	Report	Report	Report
Carbon residue ^a , % mass, max	D4530	0.050	0.050	0.050	0.050
Acid number, mg KOH/g, max	D664	0.50	0.50	0.50	0.50
Free glycerin, % mass, max	D6584	0.020	0.020	0.020	0.020
Total glycerin, % mass, max	D6584	0.240	0.240	0.240	0.240
Phosphorus content, % mass, max	D4951	0.001	0.001	0.001	0.001
Distillation temperature, 90% recovered (T90) ^b , °C, max	D1160	360	360	360	360
Sodium and potassium, combined, ppm, max	EN14538	5	5	5	5
Oxidation stability, hrs, min	EN15751	3	3	3	3

*Other test methods may be used; ^aCarbon residue shall be run on the 100% sample; ^bAtmospheric equivalent temperature

3.2.2.2. Combustion noise

The use of B100 can lower the noise level than the use of diesel oil under low and medium loads. Balasubramanian *et al.*, (2021) explained that the noise level in the use of diesel fuel is 88 dB[A] and the use of B100 fuel is 86 dB[A] at medium load. However, at high loads, the noise level of B100 is higher than that of a blend of biodiesel and pure diesel oil. It is caused by the high oxygen content in B100 which causes the fire to extinguish, causing incomplete combustion and pressure variations in the cylinder (Balasubramanian *et al.*, 2021).

3.2.3 Engine performance

3.2.3.1. Thermal Efficiency

The use of B100 resulted in higher thermal efficiency than diesel oil and blended biodiesel at all engine loads (low, medium, and high) as reported in previous studies

(Abdalla, 2018; Esonye *et al.*, 2019; Ghadikolaie *et al.*, 2019; Odibi *et al.*, 2019; Thangaraja & Srinivasan, 2019). The use of B100 includes waste cooking oil (Odibi *et al.*, 2019), vegetable (Abdalla, 2018), coconut (Thangaraja & Srinivasan, 2019), waste cooking oil (Ghadikolaie *et al.*, 2019), dan seed oil (Esonye *et al.*, 2019). Odibi *et al.*, (2019) explained that the increase in thermal efficiency in the use of B100 is due to the high input energy being converted into work. Thangraja & Srinivasan (2019) also explained that biodiesel has a high oxygen content thereby increasing combustion efficiency and lower friction losses due to better lubrication of biodiesel thereby increasing thermal efficiency, as shown in the following Figure 5. The same explanation was also reported by Esonye *et al.*, (2019) that the maximum value of BTE is obtained at the use of B100 fuel of 45% while the use of diesel fuel reaches a maximum value of 26% at full load.




Figure 4. Effect of compression ratio on cylinder pressure with B100 application (Hojati & Shirnesan, 2020).

However, other studies also reported the use of B100 resulted in lower thermal efficiency than diesel oil especially at low and medium loads, as reported by Aydin, (2020),

Hojati & Shirneshan (2020), Isik (2021), and Balasubramanian et al., (2021). The decrease in thermal efficiency can be seen in Figures 6 and Figure 7.




Figure 5. Brake thermal efficiency function engine speed (Thangaraja & Srinivasan, 2019).




Figure 6. Brake thermal efficiency function load (Aydin, 2020).




Figure 7. Brake thermal efficiency function load (Isik, 2021).

Aydin (2020) described the decrease in thermal efficiency with B100 caused by poor combustion efficiency due to spray atomization. Balasubramanian *et al.*, (2021) also explained the decrease in thermal efficiency that occurred in B100 due to its high viscosity and low heating value, as also described by Sudarmanta *et al.*, (2020). However, thermal efficiency in B100 applications can be improved through; (1) increasing the compression ratio (CR) (Hojati & Shirneshan, 2020), (2) adding ethyl proxitol and methyl proxitol catalysts to B100 (Aydin, 2020), and adding alcohols such as pentanol, butanol, and octanol to B100 (Isik, 2021). One of the results of efforts made to improve thermal efficiency is shown in **Figure 8**.

Based on **Figure 8**, the addition of alcohol pentanol (PE20) and Octanol (OC20) into B100 can increase thermal efficiency. The average thermal efficiency increase is 7% with the addition of OC20 to the B100. The inclusion of alcohol in B100 improves evaporation properties and mixing characteristics (Isik, 2021).

3.2.3.2. Specific fuel consumption (SFC)

The use of B100 resulted in higher specific fuel consumption (SFC) of blended diesel and biodiesel oil at all engine loads, as reported

by previous studies (Aydin, 2020; García-Martín *et al.*, 2018; Ge *et al.*, 2020; Ghadikolaei *et al.*, 2019; Isik, 2021; Odibi *et al.*, 2019; Santos *et al.*, 2017; Tosun & Özcanlı, 2021). The increase in specific fuel consumption is shown in **Figures 9** and **Figure 10**.

Balasubramanian *et al.*, (2021) also explained that the increase in SFC with B100 was caused by its high density and low heating value, the same statement was also explained by Ge *et al.*, (2020), Aydin (2020), Tosun & Özcanlı (2021), Santos *et al.*, (2017), Ghadikolaei *et al.*, (2019), García-Martín *et al.*, (2018). García-Martín *et al.*, (2018) further stressed that in addition to the low calorific value of B100, its high viscosity inhibits the atomization and vaporization process of the fuel thus worsening the combustion process.

However, other studies also reported that the use of B100 resulted in lower SFC than diesel oil, as reported by Abdalla (2018), Thangaraja & Srinivasan, (2019), Isik (2021), and Esonye *et al.*, (2019). Thangaraja & Srinivasan (2019) explained that the specific fuel consumption of B100 application is lower than that of pure diesel oil, it is related to basic energy, where biodiesel performs better than diesel oil, as shown in **Figure 11**.




Figure 8. Effect of adding alcohol on B100 (Isik, 2021).




Figure 9. Specific fuel consumption function load (Isik, 2021).




Figure 10. Specific fuel consumption function load (Aydin, 2020).




Figure 11. Specific fuel consumption function engine speed (Thangaraja & Srinivasan, 2019).

3.2.4 Emission

3.2.4.1. Nitrogen oxide (NOx)

Diesel engines have high NOx emissions due to their high combustion

temperature (1800 K), thus accelerating the reaction between nitrogen (N₂) and oxygen (O₂) (Aydin, 2020; Isik, 2021). The use of B100 resulted in higher NOx levels compared to

diesel oil in all engine loads, as shown in previous studies (Aydın, 2020; Esonye et al., 2019; García-Martín et al., 2018; Ge et al., 2020; Ghadikolaei et al., 2019; Hojati & Shirneshan, 2020; Isik, 2021; Santos et al., 2017; Thangaraja & Srinivasan, 2019). The increase in NOx emission is shown in Figure 12 and Figure 13.

García-Martín et al., (2018) attributed the increase in NOx emission in B100 application to the high oxygen content. The authors further stressed that the increase in NOx emission in B100 application was due to the high oxygen content and low calorific value, leading to higher fuel consumption compared to diesel fuel. Hojati & Shirneshan

(2020) also explained that the high NOx content in the B100 application was caused by the high viscosity and higher cetane number which caused a lower autoignition time which increased the temperature inside the cylinder. Meanwhile, Ghadikolaei et al., (2019) explained that biodiesel produces quite high temperatures because there are many oxygen-rich areas in the combustion chamber. Furthermore, Santos et al., (2017) also explained that high oxygen content accelerates the rate of formation of NOx emissions. Esonye et al., (2019) described the high oxygen content of B100 resulting in high temperatures that favor NOx formation.




Figure 12. NOx emission function load (Isik, 2021).




Figure 13. NOx emission function load (Hojati & Shirneshan, 2020).

However, other studies also revealed that the use of B100 resulted in lower NO_x levels than the use of diesel oil, as reported by Abdalla (2018) and Balasubramanian *et al.*, (2021). Abdalla (2018) explained that the decrease in NO_x with B100, as shown in **Figure 14**. This is caused by the high-water content, thereby lowering the combustion temperature.

3.2.4.2. Smoke

Diesel engines have high levels of smoke emissions because diesel belongs to the paraffin family with a long carbon chain. The use of B100 produces lower levels of smoke emissions compared to diesel oil at all engine loads, as revealed by Ghadikolaei *et al.*, (2019). He explained that the reduction in

smoke emissions of 57.1% with B100 is due to the high oxygen content and shorter carbon chain of biodiesel fuel.

However, another study also revealed that the use of B100 produces high levels of smoke at low and medium loads as reported by Abdalla (2018) and Balasubramanian *et al.*, (2021). The increase in smoke emission is shown in **Figure 15**.

Furthermore, Balasubramanian *et al.*, (2021) explained that the increase in smoke emissions at low and medium loads due to the rich air-fuel ratio and poor atomization so that the potential for smoke emission was greater, while at high loads, less smoke due to the availability of more oxygen, it resulted in the fuel-air ratio can be streamlined for lower smoke formation.




Figure 14. NO_x emission function BMEP (Abdalla, 2018).




Figure 15. Smoke opacity emission function load (Balasubramanian *et al.*, 2021).

4. CONCLUSION

The use of B100 in diesel engines provides advantages and disadvantages to engine performance and emissions. After a schematic literature review has been carried out, several advantages and disadvantages can be reported as follows:

- (i) **Advantages-** the use of B100 results in lower noise levels compared to diesel oil. Thermal efficiency with B100 in diesel engines can be increased due to the high oxygen content to improve the combustion process and the rate of combustion speed, although some literature describes a decrease in thermal efficiency at low and medium loads. In terms of fuel consumption, the implementation of B100 can reduce the specific fuel consumption (SFC), although some literature describes an increase in SFC. Finally, the use of B100 can reduce smoke due to its high oxygen content and short carbon chain, although some literature describes an increase in smoke values at low and medium loads.
- (ii) **Disadvantages-** the use of B100 can decrease cylinder pressure and heat release rate compared to diesel oil, but the pressure drop can be improved by increasing the compression ratio, adding alcohol, and adding a catalyst to B100. On the emission side, the use of B100 increases NO_x emissions due to the increase in combustion temperature.

That's because of the high oxygen content, although some literature also describes a decrease in NO_x.

In general, of the 12 articles that were reviewed in depth, none of them fully discussed the key performance characteristics of diesel engines which include BTE, SFC, CPSs, HRR, NO_x, and smoke. Therefore, this review provides guidance for further research to examine the use of B100 in diesel engines with all diesel engine performance variables. The research path can be developed with a wider potential to provide new arguments for different variations of diesel engine technology, variations in diesel engine dimensions, variations in B100 raw materials, and variations in test environments. In conclusion, with its weaknesses that can be covered, the B100 becomes a promising diesel engine fuel for now and the future. Besides its superior characteristics in engine performance and emissions, the use of B100 as renewable energy is an effort to realize sustainability in the transportation and industrial sectors.

5. AUTHORS' NOTE

The authors declare that there is no conflict of interest regarding the publication of this article. Authors confirmed that the paper was free of plagiarism.

7. REFERENCES

- Abdalla, I. E. (2018). Experimental studies for the thermo-physiochemical properties of biodiesel and its blends and the performance of such fuels in a compression ignition engine. *Fuel*, 212, 638–655.
- Ajith, B. S., Math, M. C., Patel, G. C. M., and Parappagoudar, M. B. (2021). Engine performance and exhaust emissions of *Garcinia gummi-gutta* based biodiesel–diesel and ethanol blends. *SN Applied Sciences*, 3(5), 1–11.
- Altaie, M. A. H. (2020). Performance and emission analysis of enriched biodiesel and its combined blends with petrodiesel. *Biofuels*, 11(3), 251-260.
- Al Husaeni, D. F., and Nandiyanto, A. B. D. (2022). bibliometric using vosviewer with publish

- or perish (using google scholar data): From step-by-step processing for users to the practical examples in the analysis of digital learning articles in pre and post Covid-19 pandemic. *ASEAN Journal of Science and Engineering*, 2(1), 19–46.
- Anderhofstadt, B., and Spinler, S. (2020). Preferences for autonomous and alternative fuel-powered heavy-duty trucks in Germany. *Transportation Research Part D: Transport and Environment*, 79, 102232.
- Arifin, A. C., Aminudin, A., and Putra, R. M. (2019). Diesel-biodiesel blend on engine performance: An experimental study. *Automotive Experiences*, 2(3), 91–96.
- Arun, S. B., Suresh, R., and Yatish, K. V. (2020). Study of performance, combustion and emission characteristics of heterogeneous catalyzed yellow oleander biodiesel on Compression Ignition (CI) engine. *Biofuels*, 11(7), 793-800.
- Atabani, A. E., Silitonga, A. S., Badruddin, I. A., Mahlia, T. M. I., Masjuki, H. H., and Mekhilef, S. (2012). A comprehensive review on biodiesel as an alternative energy resource and its characteristics. *Renewable and Sustainable Energy Reviews*, 16(4), 2070–2093.
- Aydın, S. (2020). Detailed evaluation of combustion, performance and emissions of ethyl proxitol and methyl proxitol-safflower biodiesel blends in a power generator diesel engine. *Fuel*, 270, 117492.
- Ayu, D., Aulyana, R., Astuti, E. W., Kusmiyati, K., and Hidayati, N. (2019). Catalytic transesterification of used cooking oil to biodiesel: Effect of oil-methanol molar ratio and reaction time. *Automotive Experiences*, 2(3), 73–77.
- Azizah, N. N., Maryanti, R., and Nandiyanto, A. B. D. How to search and manage references with a specific referencing style using google scholar: From step-by-step processing for users to the practical examples in the referencing education. *Indonesian Journal of Multidisciplinary Research*, 1(2), 267-294.
- Balasubramanian, D., Hoang, A. T., Papla Venugopal, I., Shanmugam, A., Gao, J., and Wongwuttanasatian, T. (2021). Numerical and experimental evaluation on the pooled effect of waste cooking oil biodiesel/diesel blends and exhaust gas recirculation in a twin-cylinder diesel engine. *Fuel*, 287, 119815.
- Bhattarai, K., Stalick, W. M., Mckay, S., Geme, G., and Bhattarai, N. (2011). Biofuel: An alternative to fossil fuel for alleviating world energy and economic crises. *Journal of Environmental Science and Health - Part A Toxic/Hazardous Substances and Environmental Engineering*, 46(12), 1424–1442.
- Bruederle, A., and Hodler, R. (2019). Effect of oil spills on infant mortality in Nigeria. *Proceedings of the National Academy of Sciences of the United States of America*, 116(12), 5467–5471.
- Bukkarapu, K. R. (2019). Comparative study of different biodiesel–diesel blends. *International Journal of Ambient Energy*, 40(3), 295–303.
- Chettouh, S., Hamzi, R., and Benaroua, K. (2016). Examination of fire and related accidents in Skikda Oil Refinery for the period 2002–2013. *Journal of Loss Prevention in the Process Industries*, 41, 186–193.
- de Souza Ferreira Filho, J. B., and Horridge, M. (2014). Ethanol expansion and indirect land use change in Brazil. *Land Use Policy*, 36, 595–604.

- Esonye, C., Onukwuli, O. D., Ofoefule, A. U., and Ogah, E. O. (2019). Multi-input multi-output (MIMO) ANN and Nelder-Mead's simplex based modeling of engine performance and combustion emission characteristics of biodiesel-diesel blend in CI diesel engine. *Applied Thermal Engineering*, 151, 100–114.
- Fadhullullah, M., Widiyanto, S. N. B., and Restiawaty, E. (2015). The potential of nyamplung (*Calophyllum inophyllum* L.) seed oil as biodiesel feedstock: Effect of seed moisture content and particle size on oil yield. *Energy Procedia*, 68, 177–185.
- Fajar, R., and Setiapraja, H. (2014). The influence of injection timing on performance characteristics of diesel engine using jatropha biodiesel with and without partial hydrogenation. *Journal of Mechatronics, Electrical Power, and Vehicular Technology*, 5(1), 59.
- Fauzan, N. A., Tan, E. S., Pua, F. L., and Muthaiyah, G. (2020). Physiochemical properties evaluation of *Calophyllum inophyllum* biodiesel for gas turbine application. *South African Journal of Chemical Engineering*, 32, 56–61.
- Firoz, S. (2017). A review: Advantages and disadvantages of biodiesel. *International Research Journal of Engineering and Technology*, 4(11), 530–535.
- Franta, B. (2021). Early oil industry disinformation on global warming. *Environmental Politics*, 30(4), 663–668.
- García-Martín, J. F., Barrios, C. C., Alés-Álvarez, F. J., Dominguez-Sáez, A., and Alvarez-Mateos, P. (2018). Biodiesel production from waste cooking oil in an oscillatory flow reactor. Performance as a fuel on a TDI diesel engine. *Renewable Energy*, 125, 546–556.
- Ge, J. C., Kim, H. Y., Yoon, S. K., and Choi, N. J. (2020). Optimization of palm oil biodiesel blends and engine operating parameters to improve performance and PM morphology in a common rail direct injection diesel engine. *Fuel*, 260, 116326.
- Ghadikolaie, M. A., Wei, L., Cheung, C. S., and Yung, K. F. (2019). Effects of engine load and biodiesel content on performance and regulated and unregulated emissions of a diesel engine using contour-plot map. *Science of the Total Environment*, 658, 1117–1130.
- Ginanjar Ahmad Zakky, W. R. M. (2020). Civil society and global governance: The indirect participation of extinction rebellion in global governance on climate change. *Journal of Contemporary Governance and Public Policy*, 1(1), 41–52.
- Hadiyanto, H., Aini, A. P., Widayat, W., Kusmiyati, K., Budiman, A., and Rosyadi, A. (2020). Multi-feedstock biodiesel production from esterification of *Calophyllum inophyllum* oil, castor oil, palm oil, and waste cooking oil. *International Journal of Renewable Energy Development*, 9(1), 119–123.
- Hamidah, I., Sriyono, S., and Hudha, M. N. (2020). A Bibliometric analysis of Covid-19 research using VOSviewer. *Indonesian Journal of Science and Technology*, 5(2), 209–216.
- Hariyanto, R. A. B., Firmansyah, R. A., Burhan, R. Y. P., and Zetra, Y. (2021). Synthesis of bio-additive for low sulphur diesel: Transesterification of soybean oil and ethylene glycol using K₂CO₃ catalyst. *Automotive Experiences*, 4(1), 44–50.
- Harnani, H. (2018). Kajian tingkat pencemaran minyak bumi akibat pengeboran ilegal

berdasarkan pemetaan sungai sumur dan fisika-kimia air studi kasus: Kecamatan Keluang Kabupaten Musi Banyuasin Sumatera Selatan. *PROMINE*, 6(2), 16–23.

- Hidayat, A., Kurniawan, W., and Hinode, H. Sugarcane bagasse biochar as a solid catalyst: From literature review of heterogeneous catalysts for esterifications to the experiments for biodiesel synthesis from palm oil industry waste residue. *Indonesian Journal of Science and Technology*, 6(2), 337-352.
- Hojati, A., and Shirneshan, A. (2020). Effect of compression ratio variation and waste cooking oil methyl ester on the combustion and emission characteristics of an engine. *Energy and Environment*, 31(7), 1257–1280.
- Isik, M. Z. (2021). Comparative experimental investigation on the effects of heavy alcohols-safflower biodiesel blends on combustion, performance and emissions in a power generator diesel engine. *Applied Thermal Engineering*, 184(2021), 116142.
- Kaniapan, S., Hassan, S., Ya, H., Nesan, K. P., and Azeem, M. (2021). The utilisation of palm oil and oil palm residues and the related challenges as a sustainable alternative in biofuel, bioenergy, and transportation sector: A review. *Sustainability (Switzerland)*, 13(6).
- Kolakoti, A., Setiyo, M., and Waluyo, B. (2021). Biodiesel production from waste cooking oil: Characterization, modeling and optimization. *Mechanical Engineering for Society and Industry*, 1(1), 22–30.
- Kumar, A., and Subramanian, K. A. (2020). Experimental investigation on effects of karanja biodiesel (B₁₀₀) on performance, combustion, and regulated and GHG emissions characteristics of an automotive diesel engine. *Biofuels*, 11(3), 239-250.
- Mahlia, T. M. I., Syazmi, Z. A. H. S., Mofijur, M., Abas, A. E. P., Bilad, M. R., Ong, H. C., and Silitonga, A. S. (2020). Patent landscape review on biodiesel production: Technology updates. *Renewable and Sustainable Energy Reviews*, 118, 109526.
- Marlina, E., Basjir, M., Ichiyanagi, M., Suzuki, T., Gotama, G. J., and Anggono, W. (2020). The role of eucalyptus oil in crude palm oil as biodiesel fuel. *Automotive Experiences*, 3(1), 33–38.
- Mudombi, S., Nyambane, A., von Maltitz, G. P., Gasparatos, A., Johnson, F. X., Chenene, M. L., and Attanassov, B. (2018). User perceptions about the adoption and use of ethanol fuel and cookstoves in Maputo, Mozambique. *Energy for Sustainable Development*, 44, 97–108.
- Nanlohy, H. Y., Riupassa, H., Rasta, I. M., and Yamaguchi, M. (2020). An experimental study on the ignition behavior of blended fuels droplets with crude coconut oil and liquid metal catalyst. *Automotive Experiences*, 3(2), 39-45.
- Odibi, C., Babaie, M., Zare, A., Nabi, M. N., Bodisco, T. A., and Brown, R. J. (2019). Exergy analysis of a diesel engine with waste cooking biodiesel and triacetin. *Energy Conversion and Management*, 198, 111912.
- Örs, İ., Sarıkoç, S., Atabani, A. E., and Ünalın, S. (2020). Experimental investigation of effects on performance, emissions and combustion parameters of biodiesel–diesel–butanol blends in a direct-injection CI engine. *Biofuels*, 11(2), 121–134.
- Pambudi, S., Ilminnafik, N., Junus, S., and Kustanto, M. N. (2021). Experimental study on the effect of nano additives γ Al₂O₃ and equivalence ratio to bunsen flame characteristic of biodiesel from nyamplung (*calophyllum inophyllum*). *Automotive Experiences*, 4(2), 51–

61.

- Panoutsou, C., Germer, S., Karka, P., Papadokostantakis, S., Kroyan, Y., Wojcieszek, M., Maniatis, K., Marchand, P., and Landalv, I. (2021). Advanced biofuels to decarbonise European transport by 2030: Markets, challenges, and policies that impact their successful market uptake. *Energy Strategy Reviews*, 34(2021), 100633.
- Rameshbabu, A., Bhaskaran, A., Sudharsanam, M., and Prabhu, A. (2020). Performance, combustion and emission characteristics of a single-cylinder constant speed compression ignition engine using soybean methyl esters. *International Journal of Ambient Energy*, 41(4), 457–461.
- Santos, T. B., Ferreira, V. P., Torres, E. A., da Silva, J. A. M., and Ordonez, J. C. (2017). Energy analysis and exhaust emissions of a stationary engine fueled with diesel–biodiesel blends at variable loads. *Journal of the Brazilian Society of Mechanical Sciences and Engineering*, 39(8), 3237–3247.
- Shao, Y., and Dessouky, M. (2020). A routing model and solution approach for alternative fuel vehicles with consideration of the fixed fueling time. *Computers and Industrial Engineering*, 142, 106364.
- Silitonga, A. S., Masjuki, H. H., Ong, H. C., Yusaf, T., Kusumo, F., and Mahlia, T. M. I. (2016). Synthesis and optimization of Hevea brasiliensis and Ricinus communis as feedstock for biodiesel production: A comparative study. *Industrial Crops and Products*, 85, 274–286.
- Sinaga, L. C. (2020). Assessing the commitment of Indonesian government towards climate change policy: The Yudhoyono presidency 2004-2014 [menilai komitmen pemerintah Indonesia terhadap kebijakan perubahan iklim: Pemerintahan presiden Yudhoyono 2004-2014]. *Jurnal Politika*, 11(2), 163–182.
- Singh, R., Singh, S., and Kumar, M. (2020). Impact of n-butanol as an additive with eucalyptus biodiesel-diesel blends on the performance and emission parameters of the diesel engine. *Fuel*, 277, 118178.
- Soares, M. de O., Teixeira, C. E. P., Bezerra, L. E. A., Paiva, S. V., Tavares, T. C. L., Garcia, T. M., de Araújo, J. T., Campos, C. C., Ferreira, S. M. C., Matthews-Cascon, H., Frota, A., Mont'Alverne, T. C. F., Silva, S. T., Rabelo, E. F., Barroso, C. X., Freitas, J. E. P. de, Melo Júnior, M. de, Campelo, R. P. de S., Santana, C. S., Cavalcante, R. M. (2020). Oil spill in South Atlantic (Brazil): Environmental and governmental disaster. *Marine Policy*, 115(2020), 103879.
- Sudarmanta, B., Mahanggi, A. A. K., Yuvenda, D., and Soebagyo, H. (2020). Optimization of injection pressure and injection timing on fuel sprays, engine performances and emissions on a developed DI 20c biodiesel engine prototype. *International Journal of Heat and Technology*, 38(4), 827–838.
- Sunaryo, S., Sesotyo, P. A., Saputra, E., and Sasmito, A. P. (2021). Performance and Fuel consumption of diesel engine fueled by diesel fuel and waste plastic oil blends: An experimental investigation. *Automotive Experiences*, 4(1), 20–26.
- Supriyadi, S., and Purwanto, P. (2018). Enhancing biodiesel from kemiri sunan oil manufacturing using ultrasonics. *E3S Web of Conferences*, 31, 2014.
- Supriyanto, Ismanto, and Suwito, N. (2019). Zeolit alam sebagai katalis pyrolisis limbah ban

bekas menjadi bahan bakar cair [natural zeolite as pyrolysis catalyst of used tires into liquid fuels]. *Automotive Experiences*, 2(1), 15–21.

Thangaraja, J., and Srinivasan, V. (2019). Techno-economic assessment of coconut biodiesel as a potential alternative fuel for compression ignition engines. *Environmental Science and Pollution Research*, 26(9), 8650–8664.

Tosun, E., and Özcanlı, M. (2021). Hydrogen enrichment effects on performance and emission characteristics of a diesel engine operated with diesel-soybean biodiesel blends with nanoparticle addition. *Engineering Science and Technology, an International Journal*, 24(3), 648–654.

Viswanathan, K., Ashok, B., and Pugazhendhi, A. (2020). Comprehensive study of engine characteristics of novel biodiesel from curry leaf (*Murraya koenigii*) oil in ceramic layered diesel engine. *Fuel*, 280, 118586.

Vohra, M., Manwar, J., Manmode, R., Padgilwar, S., and Patil, S. (2014). Bioethanol production: Feedstock and current technologies. *Journal of Environmental Chemical Engineering*, 2(1), 573–584.

Wahyu, M., Rahmad, H., and Gotama, G. J. (2019). Effect of cassava biogasoline on fuel consumption and CO exhaust emissions. *Automotive Experiences*, 2(3), 97–103.

Waluyo, B., Wardana, I. N. G., Yuliati, L., Sasongko, M. N., and Setiyo, M. (2020). The role of polar ethanol induction in various iso-octane ethanol fuel blend during single droplet combustion. *Fuel Processing Technology*, 199, 106275.

Yatish, K. V, Prakash, R. M., Ningaraju, C., Sakar, M., GeethaBalakrishna, R., and Lalithamba, H. S. (2021). Terminalia chebula as a novel green source for the synthesis of copper oxide nanoparticles and as feedstock for biodiesel production and its application on diesel engine. *Energy*, 215, 119165.

Yusoff, M. N. A. M., Zulkifli, N. W. M., Sukiman, N. L., Chyuan, O. H., Hassan, M. H., Hasnul, M. H., Zulkifli, M. S. A., Abbas, M. M., and Zakaria, M. Z. (2021). Sustainability of palm biodiesel in transportation: a review on biofuel standard, policy and international collaboration between Malaysia and Colombia. *Bioenergy Research*, 14(1), 43–60.

Zetra, Y., Sholihah, S. M. W., Burhan, R. Y. P., and Firmansyah, R. A. (2021). Synthesis and characterization of diesel lubricity enhancer through transesterification reaction of palm oil with 1, 2-ethanediol. *Automotive Experiences*, 4(2), 104–111.